



CMV Sharper Finish

"The Ironer People"



Model IFC / IFCS 2000
Model IFC / IFCS 2400 Model IFC / IFCS 3000
Model IFC / IFCS 3600

Ironers with Folder, Cross Folder, Stacker and Conveyor

Some of over 100 ironer models we manufacture



CMV Sharper Finish

IFCS shown with optional
Rear By-Pass Receiving Table



The "S" in IFCS



This stacker is a "tank". It is built to the same rigorous specifications as any of our ironers.

Features include:

- Adjustable linen stack height
- Left side or right side delivery
- Conveyor can hold four linen stacks
- Manual conveyor advance button
- Stack lift prevents accidental drops
- Stacker replaces one operator

FINISH STRONG...

IFC / IFCS Exclusive Advantages:

- Left side or right side discharge
- Rear delivery with optional Bypass Table
- Intelatrol I and II Monitoring System
- Quick Connect and Disconnect System
- Linen Reject System
- Full width Stop Cable for added safety
- Manual Operating Device
- 120"(3 m); 132"(3.3 m); 136"(3.4 m) width

IFC / IFCS Standard Features

■ The IFCS dries, irons, single lane folds, and stacks all types of linens including round tablecloths. The IFC dries, irons, and folds using less than half the floor space of a separate ironer and folder. With the IFCS stacker, only two operators are needed.

■ Five Production Sizes are available: 20" / 508 mm; 24" / 610 mm; 30" / 762 mm; and 36" / 915 mm. The larger the diameter of the ironing cylinder, the more pieces the IFC will dry, iron, and fold. Each of these Production Sizes are available in three widths: 120" / 3048 mm; 132" / 3353 mm; and 136" / 3454 mm.

■ Left or right discharge for cross folded linens. Front or rear discharge for linens with primary folds or those items that do not require folding such as napkins using optional rear bypass table.

■ The IFC and IFCS can be heated on all models by gas or steam. Electric heat is available on IFC / IFCS 2000 and 2400.

■ All IFC and IFCS models have an inverter speed drive control. The IFC and IFCS range of models begin with a speed of 20 feet per minute / 6 meters per minute and the larger Production Sizes can go as high as 100 feet per minute / 30 meters per minute.

■ The Intelatrol I and II energy saving and safety devices are installed on gas and electrically heated IFC and IFCS Models.

■ The Manual Operating Device is installed on the IFC / IFCS 3000 and IFC / IFCS 3600 models.

■ Most electrical specifications are available.

■ The OSB Smooth Fold System is installed on all IFC and IFCS models. Inverter drive is standard.

■ The Cross folder can be rolled away from the ironer for ease of repair. This means continued safe operation of the ironer and primary folder with front or rear delivery. Try to find that kind of flexibility on any other combined ironer / folder system.

Competitor's ironer / folder systems are not flexible. If their folder is need of repair, you are left with either an ironer that can only return ironed work to the front, cutting your production by more than half, or no ironer at all.

Simplicity Defined:

The IFC and IFCS Quick Connect and Disconnect

The cross folder and stacker plug directly into the ironer!

Does installation get any easier than that?

If the cross folder needs to be repaired, it can be unplugged and rolled away. This allows continued operation of the ironer and primary folder with front or rear delivery.

Cross Folder



The OSB Smooth Fold System

The OSB provides a crisp and smooth primary fold. The OSB system keeps the linen tight as the IFC or IFCS makes the primary folds.



(OSB Has Been Eliminated From The Front)

Available Options

■ Electrical Voltages

A wide variety of electrical voltages are available including 50 or 60 cycle, single or three phase.

■ Space Tight?

Can't get your new ironer into the laundry? We can! We offer two options to solve this problem. We can either build a special crate to allow the ironer to be put to get thru those narrow hallways, tight corners, and doors or we can also ship the ironer in pieces and assemble it right in your laundry.

■ Rear By-Pass Receiving Table

■ **Variety of Ironing widths including standard 120" (3 m); 132" (3.3 m); or 136" (3.4 m)**

■ Rigging Eye Bolts

■ Auxiliary Feed Basket



Model 3600 Ironer

Other Models Available from CMV Sharper Finish

We manufacture over 100 different ironer models to meet any of your needs.


Small Sized Ironers

The Mini Rite, Finish Rite, and Impress Models are single operator units that return the ironed and dried linen back to the operator. Thousands have been installed in restaurants, clubs, ships and yachts, hotels, assisted living centers, and homes around the world.



Mid Sized Ironers

The Models 1200, 1600, and 2000 are available from 85" (2.1m) to 136" (3.4m) ironing surfaces. These models can be heated by gas, steam, or electricity.



High Production Ironers

The Models 2400, 3000, and 3600 are for large laundries ironing hundreds of pounds per hour.

Built-in Primary Folder Models

The Finish Master 1600, 2000, 2400, 3000, and 3600 are ironers with built-in primary folders. Ironed and folded flatwork can be delivered to the front, or if more production is required, to another operator at the rear.

NOTE: All of the models covered in this brochure have separate Technical Data and Installation Dimension brochures giving detailed information. Contact CMV Sharper Finish for this information.

© 2014 by CMV Sharper Finish, Inc. Form CMVIFCS. In view of CMV's policy of providing the best products possible, CMV reserves the right to change specifications and appearance without notice. Contact the sales department for exact specifications, dimensions, and product approvals. CMV manufactures over 100 different ironer models that are sold throughout the world.



CMV Sharper Finish, Inc.

4500 Augusta Boulevard
Chicago, Illinois 60651-3399 U.S.A.
U.S.A. and Canada: 800-247-IRON (4766)
Telephone: 773-276-4800
Facsimile: 773-276-6878
Email: sales@cmvsharperfinish.com
www.ironerpeople.com

Distributed by: