



## Cabinet Sleeve Presses

Model 905HSA (Contoured Heads)

Model 910SAB (Flat Heads)



905HSA



910SAB

- Finish both short and long sleeves
- Foot activation for side-drying air bags
- Model 910SAB pairs with 802DBV body press
- Model 905HSA pairs with 620DBV body press
- Measuring light adjusts sleeves to proper height
- Cabinet Sleeve Presses finish a wide range of shirt sizes
- Bucks designed with padded buck plates and inflatable air bags

[www.forentausa.com](http://www.forentausa.com)

Tel: 423-586-5370 • Email: [info@forentausa.com](mailto:info@forentausa.com)

Made in USA

# Specifications

Models 905HSA, 910SAB

| Electrical connections      |                          | 905HSA              | 910SAB              |
|-----------------------------|--------------------------|---------------------|---------------------|
| 120V 1PH 50/60Hz .5AMPS     |                          | ×                   | —                   |
| 230V 1PH 50/60Hz .25AMPS    |                          | optional            | —                   |
| 208-230V 3PH 60Hz 16A 3.7KW |                          | —                   | ×                   |
| 220V 3PH 50Hz 16A 3.2KW     |                          | —                   | optional            |
| Steam and Air connection    |                          |                     |                     |
| Steam Inlet                 | NPT                      | 1/2"                | 1/2"                |
| Steam Outlet                | NPT                      | 1/2"                | 1/2"                |
| Rec. steam pressure         | PSIG                     | 100-125             | 100-125             |
|                             | kPa                      | 689-862             | 689-862             |
| Steam consumption           | BHP                      | 2                   | 2                   |
|                             | kg/hr                    | 31.8                | 31.8                |
| Compressed air              | NPT                      | 3/8"                | 3/8"                |
| Air consumption(per shirt)  | free air/cycle at 85psig | 1.7 ft <sup>3</sup> | 1.3 ft <sup>3</sup> |
|                             | free air/cycle at 586kPa | 47 ℓ                | 34 ℓ                |
| Rec. air pressure           | PSIG                     | 85                  | 85                  |
|                             | kPa                      | 586                 | 586                 |
| Weight (crated)             |                          |                     |                     |
| Shipping                    | lbs                      | 875                 | 1075                |
|                             | kg                       | 397                 | 488                 |

- 1 Steam connection
- 2 Air connection
- 3 Steam Outlet connection
- 4 Electrical connection ~for 905HSA only
- 5 Electrical connection ~for 910SAB only

## Detail Line Drawing (millimeters shown in parentheses)

