



Rotary Double Buck with Sleeve Pleaters

Model 851RDSP



- Color LCD touch screen
- Water spray and mirror standard
- Porous airbags for drying the yoke and sides of the shirt
- Footswitch control of collar clamp, vacuum and cuff clamps
- Dual-position sleeve height adjustment with auto angle orientation
- High-volume blower, duct, air heater with steam injection for sleeves
- Designed to finish the shirt body, yoke, sides, sleeves and sleeve pleats

www.forentausa.com
Tel: 423-586-5370 • Email: info@forentausa.com

Made in USA

Specifications

Model 851RDSP

Electrical connections		851RDSP
208-240V 3PH 50/60Hz 30.8-29.8 Amps 5.5kW		standard
380-415 / 460V 3PH 50/60Hz 18.5-18.1 / 17.7 Amps 5.5 kW		optional
380-415 / 460V 3PH 50/60Hz 20.7 Amps 5.5 kW, with/240V Neutral wire		optional
Steam and air connections		
Steam inlet	NPT	1/2"
Steam outlet (total of 3 outlets)	NPT	1/2"
Recommended steam pressure	PSIG kPa	115-125 793-862
Steam consumption @ 125 psig (862 kPa)	lb/hr	86
	kg/hr	39
	BHP	2.5
Compressed air	NPT	3/8"
Air consumption/shirt	free air/cycle @ 80 psig	3.6 ft ³
	free air/cycle @ 552 kPa	102 liter
Recommended air pressure	PSIG kPa	80 552
Water connection (for water spray)	NPT	1/4"
Weight (crated)		
Shipping	lbs	2300
	kg	1043

- 1 Steam connection
- 2 Steam outlets
- 3 Control panel
- 4 Air connection
- 5 Electrical connection
- 6 Water connection (For water spray)

Detail Line Drawing

(millimeters shown in parentheses)

