



Small Laundry Presses "VS" Series

Models A19/A3516/A27/A32/A450

Models ATA19/ATA3516/ATA27/ATA32/ATA450



Model A19VS • Safety Bar Activated



Model ATA3516VS • Two Button Activated

- Fast head closing for maximum operator efficiency
- Most models available steam or electrically-heated
- Models 32VB and 27VCY designed for shirt finishing
- Multiple buck sizes and configurations to choose from
- No electricity hook-up needed on steam-heated models
- Available in either bar or two button activated closing system
- Patented mechanism provides reliable service at minimal operating costs
 - Options include Iron Tray Attachment, Water Spray and Air Timer

Forenta's small laundry presses have long been considered the industry standard for speed and efficiency. Available in both steam or electrically-heated models, these presses are offered in multiple buck sizes and with various options. This patented, time-tested design provides simplicity and reliability and is backed by one of the best warranties in the industry.

www.forentausa.com

Tel: 423-586-5370 • Email: info@forentausa.com

Made in USA

"VS" SERIES SPECIFICATIONS

Steam connections:

- 1/2 NPT for supply and condensate
- 100-125 psi (0.69-0.86 MPa)
- Steam consumption at 100 psi(0.69 MPa):
- 0.75 BHP(26 lb/hr)(11.7 kg/hr)

Compressed air connection:

- 3/8 NPT
- Recommended Air Pressure: 68 psi (0.47 MPa)
- Free air/cycle at 68 psi (0.47 MPa): 0.23 cubic feet (6.5 liters)

Electrical connection: (A19VSE & ATA19VSE)

- 230 VAC single-phase, 50/60 Hz, 1600watts
- Approx. Consumption/Hour 0.8 KWH

Electrical connection: (A27VCYE & ATA27VCYE)

- 230 VAC single-phase, 50/60 Hz, 2650watts
- Approx. Consumption/Hour 1.35 KWH

Electrical connection: (A32VBE & ATA32VBE)

- 230 VAC single-phase, 50/60 Hz, 2975watts
- Approx. Consumption/Hour 0.8 KWH

Electrical connection: (A450MILE & ATA450MILE)

- 230 VAC single-phase, 50/60 Hz, 4800watts
- Approx. Consumption/Hour 2.4 KWH

Optional hand iron electrical connection (external wiring, not part of press internal wiring):

- 115 VAC or 230 VAC single-phase, 50/60 Hz
- Conduit connection
- 800 watts
- Approximate hourly consumption: 0.5 KWH

Optional water spray cold water connection:

- 1/4 NPT
- 40-80 psi (0.3-0.55 MPa)
- 1 gallon/minute (3.8 liter/minute)

Optional Attachment Kits

K-211 Steam/Electric Iron Attachment, 115 Volt

K-463 Steam/Electric Iron Attachment, 230 Volt

K-212 All-Steam Iron Attachment

K-208 Water Spray

K-225 Timer Kit for "A" models

K-594 Timer Kit for "ATA" models

K-240 Corner Table

BUCK DIMENSIONS (unpadded)

