

VENDED
GALAXY™ 600
WASHER-EXTRACTORS



HUEBSCH®: YOUR SMART LAUNDRY PARTNER

Success in the laundromat business is determined long before the “Open” sign is switched on. That’s why it’s paramount to work with an experienced partner. With more than 100 years in the laundry business and a distribution network ranked at the top of the industry*, Huebsch® truly is your smart laundry partner, guiding you every step of the way.

*According to an August 2014 Leede Research Customer Value Analysis.

GALAXY™ 600: THE PINNACLE OF CONVENIENCE AND CONTROL

Your laundry is selling convenience and a high-quality wash. With Huebsch Galaxy™ 600 controls, your laundromat gives customers a user-friendly platform and the flexibility to tailor washes the way they like. Best of all, that flexibility brings additional revenue-generating opportunities. Galaxy 600 benefits include:

- 200 G-Force final extract to reduce drying times, lower utility bills and increase customer satisfaction
- 24 Cycle combinations for customers to choose from
- Time-of-day pricing to help manage peak-period business and attract new customers
- Multi-level vend and cycle modifiers to increase revenue
- Huebsch Command™ compatible for remote management ease

Control Aesthetics Options

Citron

Cityscape

Slate





HUEBSCH COMMAND™ READY

The Huebsch Command™ Technology Suite changes the way you'll run your laundry business. Get unprecedented power over all your business data—

financial, operational, customer, service machine and maintenance—in a single 360-degree control center, enabling you to make informed business decisions and be in command of your business's growth.

- **Owner Dashboard**
- **Customer App**
- **Point of Sale (POS) System**
- **Customer Relationship Management (CRM)**

DISCOVER SMART, REVOLUTIONARY, EFFICIENT TECHNOLOGY

Uses 33% Less Electricity & 17% Less Water than Two-Speed Models

Our advanced inverter drive technology and improved cylinder and sump system design optimize water use, while reducing non-wash water below the cylinder.

High-Speed Extraction Reduces Drying Time

Our improved technology spins up to 200 G-Force, removing more water. This means shorter dry times and lower energy bills.

Advanced Leak Detection Eliminates Wasted Water

Patented Water Guardian™ leak detection uncovers leaks in both the drain and fill valves, eliminating wasted water—and resources.

BACKED BY OUR 10-YEAR LIMITED WARRANTY



Our Galaxy 600 washer-extractors are manufactured at our Ripon, Wisconsin headquarters. We offer an industry-leading, transferable warranty on every product:*

- Frame
- Outer Tub
- Cylinder
- Shaft
- Seals and Bearings
- Bearing Housing

*Vended products only within the USA and Canada. All other markets consult with your authorized distributor.

VENDED GALAXY™ 600 WASHER-EXTRACTORS

Models		HCT020	HCT030	HCT040	HCT060	HCT080	HCT100	
Control Options		Galaxy™ 600	Galaxy™ 600	Galaxy™ 600	Galaxy™ 600	Galaxy™ 600	Galaxy™ 600	
Capacity – lb (kg)		20 (9)	30 (13.6)	40 (18)	60 (27)	80 (36)	100 (45)	
Overall Width – in (mm)		26 (660)	29 (737)	30.6 (777)	34.1 (866)	41.5 (1054)	41.5 (1054)	
*Overall Depth – in (mm)		30.9 (785)	35.3 (897)	42.3 (1074)	44.7 (1135)	47.1 (1196)	51.1 (1298)	
Overall Height – in (mm)		43 (1092)	45 (1143)	47.2 (1199)	49.9 (1267)	57.2 (1453)	57.2 (1453)	
Cylinder Diameter – in (mm)		21 (533)	24 (610)	26.3 (668)	30 (762)	36 (914)	36 (914)	
Cylinder Depth – in (mm)		13.8 (351)	16 (406)	20.3 (516)	22 (559)	21.9 (556)	25.9 (658)	
Cylinder Volume – cu ft (liters)		2.8 (79)	4.2 (119)	6.3 (178)	9 (225)	12.9 (365)	15.2 (430)	
Door Opening Size – in (mm)		11.6 (295)	14.3 (363)	16.3 (414)	16.3 (414)	18.5 (470)	18.5(470)	
Door Bottom to Floor – in (mm)		14.4 (366)	14 (356)	14.6 (371)	14.9 (378)	17.9 (455)	17.9 (455)	
Water Inlet Connection – in (mm)		2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	4 x 0.75 (19)	4 x 0.75 (19)	4 x 0.75 (19)	
Drain Diameter – in (mm)		1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	
Drain Height to Floor – in (mm)		3.9 (99)	4.3 (109)	4.5 (114)	4.9 (124)	5.1 (130)	5.1 (130)	
Motor Power Consumption – HP(kW)		1 (0.75)	1 (0.75)	2 (1.5)	3 (2.2)	5 (3.7)	5 (3.7)	
Total # of Speeds		6, 9	6, 9	6, 9	6, 9	6, 9	6, 9	
Cylinder Speeds – RPM (G-Force)		Gentle	37 (0.4)	34 (0.4)	33 (0.4)	31 (0.4)	28 (0.4)	28 (0.4)
		Wash	51 (0.8)	48 (0.8)	46 (0.8)	43 (0.8)	39 (0.8)	39 (0.8)
		Distribution	92 (2.5)	86 (2.5)	82 (2.5)	77 (2.5)	70 (2.5)	70 (2.5)
		Very Low	301 (27)	282 (27)	269 (27)	252 (27)	230 (27)	230 (27)
		Low	518 (80)	485 (80)	464 (80)	434 (80)	396 (80)	396 (80)
		Medium	579 (100)	542 (100)	518 (100)	485 (100)	443 (100)	443 (100)
		High	648 (125)	606 (125)	579 (125)	542 (125)	495 (125)	495 (125)
		Very High	710 (150)	664 (150)	635 (150)	594 (150)	542 (150)	542 (150)
		Ultra High	819 (200)	766 (200)	733 (200)	686 (200)	626 (200)	568 (165)
** Voltage/ Circuit Breaker - FLA	B	120/60/1	15-9	15-12	20-15	N/A	N/A	N/A
	X	200-240/50-60/1/3	15-4 (1 Ph) 15-3 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-11 (1 Ph) 15-7 (3 Ph)	20-15 (1 Ph) 15-9 (3 Ph)	20-16 (1 Ph) 15-10 (3 Ph)
	Y	200-240/60/1/3 (Pump Drain Only)	15-4 (1 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	N/A	N/A	N/A
Shipping Dimensions Approx. – in (mm)		Width	28 (711)	31.5 (800)	32.5 (826)	37.5 (953)	44 (1118)	44 (1118)
		Depth	33.8 (859)	38.3 (973)	43.5 (1105)	46.9 (1191)	54.5 (1384)	58.5 (1486)
		Height	49.4 (1255)	51.3 (1303)	53.6 (1361)	56.3 (1430)	59.6 (1514)	59.6 (1514)
Net Weight – lb (kg)		340 (154)	440 (200)	540 (245)	680 (308)	1250 (567)	1280 (581)	
Shipping Weight – lb (kg)		380 (172)	480 (218)	580 (263)	720 (327)	1300 (590)	1330 (603)	
Slat Crate Shipping Weight – lb (kg)		460 (209)	580 (263)	680 (308)	840 (381)	1430 (649)	1460 (662)	
***Agency Approvals		cULus	cULus	cULus	cULus	cULus	cULus	

*Overall depth includes vacuum breaker to door handle.

** Circuit breaker and amp draw data shown are for models without electric heat. Consult factory for other configurations. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines.

***Agency approvals may vary depending on configuration. Steam connection requires ½" N.P.T.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.